SPECIFICATIONS: 2020 Commercial ZTrak™ Mowers

WARRANTY

Duration

Type

NOT READILY **E** Series Z930M **Z945M EFI /Z955M EFI Z950M** 7250 **Z920M Z915E** MODEL \$850 9150 ENGINE 27.0 HP (20.1 kW)^{3.5} / 29.0 HP (21.6 kW)^{3.5} @ 3600 RPM 25.5 HP (19.0 kW)^{2.3} @ 3600 RPM 23.5 HP (17.5 kW)^{2.3} @ 3600 RPM 27.0 HP (20.1 kW)23 @ 3600 RPM 25.0 HP (18.6 kW) @ 3600 RPM Certified Horsepower FX850V ECV850 EFI / ECV860J EFI Engine Mode CV747 FX730V F801V 824 cc / 824 cc 852 cc 747 cc 776 00 852 cc Displacement Two Two Two Two Cylinders Full flow, replaceable Oil Filter Full pressure Full pressure Full pressure Lubrication Full pressure Full pressure Cooling Heavy-duty canister type with safety Heavy-duty canister type with Heavy-duty canister type with safety Heavy-duty canister type with Heavy-duty canister type with Air Cleaner safety element safety element safety element element **FUEL SYSTEM** Gas Gas Fuel Type Gas 11.5 U.S. gallons (43.5 L) Fuel Tank Capacity **ELECTRICAL SYSTEM** 20 amp 20 amp Charge System 15 amp 20 amp 20 amp 17 Volt 12 Volt 12 Volt 12 Volt Battery Voltage 12 Volt Standard, digital Standard, digital Standard, digital Standard, digital Standard, digital Hour Meter Brake-N-Go (hand) Brake-N-Go (hand) Brake-N-Go (hand) Brake-N-Go (hand) Brake-N-Go (hand) Operator Presence Starting System DRIVE TRAIN Tuff Torq heavy-duty integrated Tuff Torq heavy-duty integrated Tuff Torg heavy-duty integrated Tuff Torq heavy-duty integrated Tuff Torq heavy-duty integrated Hydraulic Pumps piston pump Tuff Torq heavy-duty integrated piston pump Tuff Torg heavy-duty integrated piston wheel motor piston pump Tuff Torq heavy-duty integrated piston wheel motor piston pump Tuff Torq heavy-duty integrated piston wheel motor piston pump Tuff Torg heavy-duty integrated piston Wheel Motors wheel motor piston wheel motor 5.9 U.S. qt (5.58 L) 5.9 U.S. qt (5.58 L) 5.9 U.S. at (5.58 L) 5.9 U.S. qt (5.58 L) 5.9 U.S. qt (5.58 L) Hydraulic Capacity 0 - 10 mph (0-16.1 km/h) Travel Speed Forward 0 - 4.5 mph (0-7.2 km/h) Travel Speed Reverse 0 - 4.5 mph (0-7.2 km/h) PTO Electro-magnetic (225 lb. ft.) Electro-magnetic (225 lb. ft.) Electro-magnetic (200 lb. ft.) Electro-magnetic (200 lb. ft.) Electro-magnetic (225 lb. ft.) Туре V-belt V-belt V-helt V-belt V-belt Drive BRAKES Internal wet disk integrated in the Park Brake transmisson transmisson Hand brake Hand brake Hand brake Park Brake Actuation Hand brake Hand brake MOWER DECKS 48, 54, 60 in. (121.9, 137.2, 152.4 cm) 60, 60 MOD (152.4, 152.4 MOD) / 60, 60 MOD, 72 in. 54, 54 in. MOD / 60, 60 in. MOD (137.2, 137.2 MOD, 152.4, 152.4 60, 60 MOD, 72 in.(152.4, 152.4 MOD, 182.9 cm) 48, 48 MOD, 54, 60 in. (121.9, 121.9 Available Widths / Type MOD, 137.2, 152.4 cm) (152.4, 152.4 MOD, 182.9 cm) 7-Iron PRO (One-piece stamped steel with reinforcements) 7-Iron PRO (One-piece stamped steel with reinforcements) 7-Iron PRO (One-piece stamped 7-Iron PRO (One-piece stamped steel with reinforcements) 7-Iron II (One-piece stamped steel with reinforcements) Deck construction steel with reinforcements) 7-gauge (0.177 in.) Deck thickness 1.0 in. to 5.5 in. (2.5 cm - 13.9 cm) 1.0 in. to 5.5 in. (2.5 cm - 13.9 cm) 1.0 in. to 5.5 in. (2.5 cm - 13.9 cm) 1.0 in. to 5.5 in. (2.5 cm - 13.9 cm) / 1.0 in. to 5.5 in. (2.5 cm - 13.9 cm) / Height-of-Cut Range / Increment / 0.25 in. (.6 cm) 0.25 in. (.6 cm) 0.25 in. .6 cm) 0.25 in. (.6 cm) BLADES Approximately 18,000 fpm Tip Speed Three Three Three Three Number WHEELS AND TIRES 24x9.5-12 Turf (48"), 24x12-12 Turf (54", 60"); 24x12-12 X TWEEL TURF 24x9.5-12 Turf (48"), 24x12-12 Turf (54", 60"); 24x12-12 X TWEEL TURF (54", 60") 24x12-12 Turf; 24x12-12 X TWEEL TURF 24x12-12 Turf; 24x12-12 X TWEEL 24x12-12 Turf; 24x12-12 X TWEEL TURF Drive (Rear) Tires (54", 60" Flat Free Flat Free Flat Free Caster Wheel Type Pneumatio Flat Free 13x6.5-6 13x6.5-6 13x6.5-6 13x5-6 13x6.5-6 Caster Wheel Size DIMENSIONS 84 in. (213.4 cm) 84 in. (213.4 cm) 84 in. (213.4 cm) 84 in. (213.4 cm) Overall Length 84 in. (213.4 cm) 74, 86 in. (188, 218.4 cm) with 74, 86 in. (188, 218.4 cm) with chute 62, 68, 74 in. (157.5, 172.7, 188 cm) 62, 68, 74 in. (157.5, 172.7, 188 cm) 74, 86 in. (188, 218.4 cm) with Overall Width (chute down) chute down with chute down with chute down chute down 73 in. (185.4 cm) with ROPS up; 47 in. (119.4 cm) with ROPS down 73 in. (185.4 cm) with ROPS up; 47 in. (119.4 cm) with ROPS down 73 in. (185.4 cm) with ROPS up; 47 in. (119.4 cm) with ROPS down 73 in. (185.4 cm) with ROPS up; 47 in. (119.4 cm) with ROPS down 73 in. (185.4 cm) with ROPS up; 47 Height in. (119.4 cm) with ROPS down 1178 lb (534.3 kg) - Z915B 60" 1340 lb (607.8 kg) - Z960R 72" Weight (with Fluids) 1283 lb (582 kg) - Z920M 60" 1365 lb (619.2 kg) - Z930M 60" 1365 lb (619.2 kg) - Z950M 60"

Hour and/or usage limitations apply and vary by model. See the WARRANTY FOR NEW JOHNDEERE TURF AND UTILITY EQUIPMENT at dealer for details. 20 3600 RPM engine manufacturer certified gross power tested in accordance with SAE J1995. The engine horsepower and torque information are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the engine manufacturer web site for additional information. Engine HP at Gross SAE J1995, PS, rated at 3000 RPM [2997R – displacement 100.2 cu.in. (1.64L)]. 360 RPM engine manufacturer certified gross power per SAE J1940, tested in accordance with SAE J1995. Engine HP at Gross SAE J1995, PS, rated at 3200 RPM [2994R – displacement 77.3 cu.in. (1.27 L)].

36 months or 1200 hours, whichever

comes first, no hour limitation for the first 24 months

Single Source Commercial

36 months or 1200 hours, whichever comes first, no hour

Single Source Commercial

limitation for the first 24 months

36 months or 1200 hours, whichever

first 24 months

Single Source Commercia

comes first, no hour limitation for the

36 months or 1200 hours, whichever

comes first, no hour limitation for

the first 24 months

Single Source Commercial

36 months or 1200 hours, whichever

romes first, no hour limitation for

the first 24 months Single Source Commercial

¹ GAS engines - The engine horsepower and torque information are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the engine manufacturer's web site for additional information.

Quote #: 11948

Invoice Date:

Print Date: 6/17/2021

BILLING ADDRESS

CITY OF LEBANON WATER WASTE 312 WEST ST. LOUIS STREET FRANON II 62254

LEBANON, IL 62254 United States (618) 977-6786



SHIPPING ADDRESS

CITY OF LEBANON WATER WASTE 312 WEST ST. LOUIS STREET LEBANON, IL 62254 United States (618) 977-6786

Qty	ltem No.	Item Description		Your Price	Amount
1.00	092836	GRAVELY PRO-TURN MODEL=991130 SERIA Year/Make/Model; 2021/GRAVELY/99 External Color; Hours1; 0	AL=092836	8,021.23	8,021.23
			Total Invoice — Subtotal:	And the second of the second	8,021.23
			Total:		8,021.23
			Shipping:		0.00
			Sales Tax:		0.00
		•	Total Due:		8,021.23
_ Tracking	o No.		Payment Received:		0.00
		YOU SAVED: \$1,760.76	Balance Due:		8,021,23

THANK YOU FOR YOU BUSINESS!! NO RETURNS ON SPECIAL ORDER

NO RETURNS ON SPECIAL ORDER ITEMS.
NO RETURNS ON ELECTRICAL ITEMS.
NO RETURNS AFTER 14 DAYS ON ALL OTHER PARTS.
ALL OTHER RETURNS SUBJECT TO 25% RESTOCK FEE.

ALL EQUIPMENT SALES FINAL

Sustomer)		
	•	
	;	