

Customer:

Quotes are valid for 30 days from the creation date or upon contract expiration, whichever occurs first.

A Purchase Order (PO) or Letter of Intent (LOI) including the below information is required to proceed with this sale. The PO or LOI will be returned if information is missing.

Vendor: Deere & Company	For any questions, please contact:
2000 John Deere Run Cary, NC 27513	Jerrod Haas
Signature on all LOIs and POs with a signature line	Shiloh Valley Equipment Co. 4050 East Highway 161 Belleville, IL 62221
Contract name or number; or JD Quote ID	Tel: 618-744-0433
 Sold to street address Ship to street address (no PO box) 	Fax: 618-744-0443 Email: lgsales@shiloh-valley.com
Bill to contact name and phone number	
Bill to address	
Bill to email address (required to send the investment of the inve	voice and/or to obtain the tax
Membership number if required by the contract	ct

Quotes of equipment offered through contracts between Deere & Company, its divisions and subsidiaries (collectively "Deere") and government agencies are subject to audit and access by Deere's Strategic Accounts Business Division to ensure compliance with the terms and conditions of the contracts.



ALL PURCHASE ORDERS MUST BE MADE OUT
TO (VENDOR):
Deere & Company
2000 John Deere Run
Cary, NC 27513
FED ID: 36-2382580
UEID: FNSWEDARMK53

ALL PURCHASE ORDERS MUST BE SENT TO DELIVERING DEALER: Shiloh Valley Equipment Co. 4050 East Highway 161 Belleville, IL 62221 618-744-0433 shilohvalley@shiloh-valley.com

Quote Summary

Prepared For: CITY OF LEBANON 312 W SAINT LOUIS ST LEBANON, IL 62254 Business: 618-537-4976 streets@lebanonil.org			:	2	Valle 1050 Pho	Delivering Dealer: ey Equipment Co. Jerrod Haas East Highway 161 Belleville, IL 62221 ne: 618-744-0433 @shiloh-valley.com
			Cre Mod	Quote I ated O lified O ion Dat	n: n:	29013627 09 June 2023 23 June 2023 10 July 2023
Equipment Summary	Suggested List	Selling Price		Qty		Extended
JOHN DEERE Z950M ZTrak	\$ 11,474.00	\$ 7,687.58	Х	1	=	\$ 7,687.58
Contract: IL PSD Mowers 4018512 (PC Price Effective Date: September 4, 20	,					

Equipment Total

\$ 7,687.58

Trade In Summary	Qty Each	Extended
2014 JOHN DEERE X758 - 1M0X758AHEM020652	1 \$4,500.00	\$ 4,500.00
PayOff		\$ 0.00
Total Trade Allowance		\$ 4,500.00
Trade In Total		\$ 4,500.00
* Includes Fees and Non-contract items	Quote Summary	
	Equipment Total	\$ 7,687.58
	Trade In	\$ (4,500.00)
	SubTotal	\$ 3,187.58
	Est. Service Agreement Tax	\$ 0.00
	Total	\$ 3,187.58
	Down Payment	(0.00)
Salesperson : X	Accepted By	: X

Confidential



ALL PURCHASE ORDERS MUST BE MADE OUT TO (VENDOR): Deere & Company 2000 John Deere Run Cary, NC 27513 FED ID: 36-2382580 UEID: FNSWEDARMK53

ALL PURCHASE ORDERS MUST BE SENT TO DELIVERING DEALER: Shiloh Valley Equipment Co. 4050 East Highway 161 Belleville, IL 62221 618-744-0433 shilohvalley@shiloh-valley.com

 Rental Applied
 (0.00)

 Balance Due
 \$ 3,187.58

Accepted By : X _____



Selling Equipment

Quote Id: 29013627 Customer Name: CITY OF LEBANON

ALL PURCHASE ORDERS MUST BE MADE OUT

TO (VENDOR): Deere & Company 2000 John Deere Run Cary, NC 27513 FED ID: 36-2382580 UEID: FNSWEDARMK53

ALL PURCHASE ORDERS MUST BE SENT TO DELIVERING DEALER:

Shiloh Valley Equipment Co. 4050 East Highway 161 Belleville, IL 62221 618-744-0433 shilohvalley@shiloh-valley.com

	JO	HN	DEERE Z	950M ZTra	ak		
Hours:						Sug	gested List *
Stock Nu	umber:					\$	11,474.00
Contract	: IL PSD Mowers 4018512	2 (P	G 97 CG 22)		Se	elling Price *
Price Eff	ective Date: September	4, 2	017			:	\$ 7,687.58
		* Pri	ce per item	- includes F	ees and No	n-contract i	tems
Code	Description	Qty	List Price	Discount%	Discount	Contract	Extended
		-			Amount	Price	Contract Price
0694TC	Z950M ZTrak	1	\$ 10,999.00	33.00	\$ 3,629.67	\$ 7,369.33	\$ 7,369.33
		Star	dard Option	s - Per Unit			
001A	United States/Canada	1	\$ 0.00	33.00	\$ 0.00	\$ 0.00	\$ 0.00
1036	24x12x12 Pneumatic Turf Tire for 54 In. and 60 In. Decks	1	\$ 0.00	33.00	\$ 0.00	\$ 0.00	\$ 0.00
1504	60 In. Side Discharge Mower Deck	1	\$ 0.00	33.00	\$ 0.00	\$ 0.00	\$ 0.00
2093	Fully Adjustable Suspension Seat with Armrests (24" High Back)	1	\$ 475.00	33.00	\$ 156.75	\$ 318.25	\$ 318.25
	Standard Options Total		\$ 475.00		\$ 156.75	\$ 318.25	\$ 318.25
			• • • •				
	Value Added Services Total		\$ 0.00			\$ 0.00	\$ 0.00
Total Selli	ing Price		\$ 11,474.00		\$ 3,786.42	\$ 7,687.58	\$ 7,687.58



Product features, prices and specifications are based on published information at the time of publication and are subject to change without notice. All trademarked terms, including John Deere, the leaping deer symbol and the colors green and yellow used herein are the property of Deere & Company, unless otherwise noted. Products, product features, and other content on this site may only be accurate for products marketed and sold in North America.

Copyright © 1994- 2023 Deere & Company. All Rights Reserved.

File Created: 23-Jun-2023

2023 JOHN DEERE Z950M ZTrak

Key Features

Powerful 27-hp (20.1-kW) commercial-grade engine delivers class-leading performance and efficiency

The Z950M and Z950R are powered by an air-cooled, vertical shaft engine:

- 27-hp (20.1-kW) gas engine
- Engine features include:
- Overhead valve design
- More horsepower and torque per cubic inch of displacement
- Better fuel efficiency
- · Full-pressure lubrication with full-flow filter
- Reduces engine wear by ensuring proper lubrication, even when operating on hillsides or uneven terrain
- Oil filter helps keep oil clean for increased engine life
- V-twin big block design
- Vertical shaft
- · Easy-access, dual-element air filter with quick-release latch
- 15-amp alternator
- Fuel pump

· Complies with strict Environmental Protection Agency (EPA) and California Air Resources Board (CARB) emission standards without loss of horsepower or torque

- Aluminum block engines
- Effectively dissipate heat
- Lightweight and strong construction
- · Extend engine life due to elimination of debilitating engine temperatures
- Air-cooled engine design



Z950M and Z950R engine

Base Equipment On: Z950M, Z950R

Air cleaner filters out dust that can damage an engine

ZTrak™ Z900 Mowers are equipped with a dual-element, canister-style air filter, easily accessible from the rear of the machine without tools.

- The filtration system pulls clean air from above the engine, in turn filtering out the dust that can damage an engine over time.
- Filters are extremely easy to change when required.
- Pre-cleaner provides more protection against contamination in dusty and dirty applications.









Air cleaner cover removed

Base Equipment On: Z950M, Z950R

Mow all day on a single tank of fuel with efficient and easy-to-fill fuel tank

The ZTrak[™] Z900 Mowers are equipped with one single-fill, top-draw fuel tank:

- 11.5-U.S. gal. (43.5-L) capacity enables operators to mow all day without refueling.
- The fuel gauge makes it quick and easy to see how much fuel is in the tank.
- Top draw provides added safety.
- A large fuel-filler neck is angled to make it easy for an operator to complete the fueling process.

Under normal conditions, load, and operation, fuel consumption for the Z900 ZTrak Mowers is 1.5 U.S. gph (5.7 L/hr) to 2.2 U.S. gph (8.3 L/hr), depending on the horsepower and conditions.



Fuel tank and filler neck

Base Equipment On: Z950M, Z950R

Key Features




Fuel filler neck

Three-year, bumper-to-bumper warranty









Base Equipment On: Z915E, Z920M, Z930M, Z945M EFI, Z950M, Z955M EFI, Z960M, Z930R, Z950R, Z955R EFI, Z970R E and M Series 3-year, 1200-hour bumper-to-bumper warranty

An exclusive 2-year, unlimited hour/3-year, 1200-hour (whichever comes first) bumper-to-bumper warranty is standard for all John Deere E and M Series Mowers. The warranty is best in its class and places John Deere at the forefront of commercial mowing. It is also hassle free, with one company handling all of the paperwork.

NOTE: 36 months or 1200 hours, whichever comes first. For the first 24 months, there is no hour limitation.

Base Equipment On: Z915E, Z920M, Z930M, Z945M EFI, Z950M, Z955M EFI, Z960M, Z930R, Z950R, Z955R EFI, Z970R **R Series 3-year, 1500-hour bumper-to-bumper warranty**

An exclusive 2-year, unlimited hour/3-year, 1500-hour (whichever comes first) bumper-to-bumper warranty is standard on all John Deere R Series mowers. The warranty is best in the industry and puts John Deere at the forefront of commercial mowing. It is also hassle free, with one company handling all of the paperwork.

NOTE: 36 months or 1500 hours, whichever comes first. For the first 24 months, there is no hour limitation.

Base Equipment On: Z915E, Z920M, Z930M, Z945M EFI, Z950M, Z955M EFI, Z960M, Z930R, Z950R, Z955R EFI, Z970R **Mower decks are safety certified**



Mowers decks are evaluated by the manufacturer (John Deere Turf Care) and conform to American National Standards Institute (ANSI) B71.4 2004 safety certification specifications for commercial turf care equipment.

54-in. (137-cm) 7-Iron PRO Mower Deck

Base Equipment On: Z915E, Z920M, Z930M, Z945M EFI, Z950M, Z955M EFI, Z960M, Z930R, Z950R, Z955R EFI, Z970R

Key Features

Heavy-duty frame provides strength and durability





The durability features of the frame are as follows:

- Heavy-duty, thick-gauge, steel channel mainframe for strength and durability
- Cast I-beam caster arms to handle the beating and pounding professional mowers receive
- Wide-open access for maintenance and cleaning

Z970R shown with optional X® Tweel® Turf airless radial tire technology

Base Equipment On: Z915E, Z920M, Z930M, Z945M EFI, Z950M, Z955M EFI, Z960M, Z930R, Z950R, Z955R EFI, Z970R **Two-piece rear bumper provides protection**



A steel rear bumper provides protection for the machine. The bumper is made of two pieces, making it easy to remove and install when using a material collection system (MCS).

A rear hitch can be added to the steel bumper for towing purposes. ZTrak E, M, and R Series Mowers can tow up to 400 lb (181.4 kg).

Michelin, X, and Tweel are trademarks of Michelin North America, Inc.

Illustration of ZTrak™ mower rear bumper

Base Equipment On: Z915E, Z920M, Z930M, Z945M EFI, Z950M, Z955M EFI, Z960M, Z930R, Z950R, Z955R EFI, Z970R

Product Specification Details :

Man koflan:tDeer re Z950M (Model year 2023) Model	
Engine	
Manufacturer/Model	FX850V
Power	Gross at 3,600 rpm
	27 hp
	20.1 kW
Displacement	52 cu in.
	852 cc
Cylinders	Тwo
Crankcase capacity	With filter, 2.4 U.S. qt
	2.3 L
Oil filter	Full flow, replaceable
Lubrication	Full pressure
Cooling	Air
Air cleaner	Heavy-duty canister type with safety element
Pre-cleaner	Yes



Fuel consumption Gasoline Fuel consumption Gasoline Fuel consumption Gasoline Fuel consumption Gasoline Fuel cansumption Gasoline Fuel tank capacity 15 U.S. gal. Fuel tank switch/dutu-off vaive Yes Electrical system 20 amp Battery voltage 21 V Cold cranking amp 300 amp Battery voltage 21 V Cold cranking amp 300 amp Battery voltage 21 V Cold cranking amp 300 amp Divertain Transmission Hydraulic propeo Wheel motors Tuff Torq heavy-duty integrated piston wheel motor Transmission Hydraulic appearity Hydraulic capacity 5.6 L Hydraulic appearity 5.9 U.S. qt Hydraulic capacity 5.9 U.S. qt Hydraulic appearity 2.9 U.S. qt Filter Internal, replaceable Trans Tuff Torq heavy-duty integrated piston wheel motor Type 26.4 L Hydraulic all cooler Filter Tuff Torq heavy-duty integrated piston wheel motor Tork 24.72.12 Park 24.12 Park <th>Fuel system</th> <th></th>	Fuel system	
Fuel consumption Under normal conditions, load, operation, and operation and operating conditions in 1-11 of U.S. gal./hri - 2-7 2. Unr - 2-7 2. Unr Fuel tank capacity - 45. 7.2 Unr Fuel tank switch/shut-off valve Yes Electrical system - 20 amp Charge system 20 amp Battery voltage 20 amp Cold crashing amp 300 amp Operator presence starting system Bracke-N-Go (hand) Divertain Hydrostatic Transmisoin Hydrostatic Hydraulic pumps	-	Gasoline
Fuel tank capacity 11.5 U.S. gal. Fuel tank switch/shut-off valve Yes Electrical system 20 amp Electrical system 20 amp Batery voltage 20 amp Operatory presence starting system Brake-N-Go (hand) Dyrwaran Hydrostatic Hydraulic capacity Face N-Go (hand) Drivetrain		dependent on loads and operating conditions
Fuel tank switch/enu/eff valueYesElectrical system20 ampCharge system20 ampBattery voltage12 VCold cranking ampStandard, digitalOperator presence starting systemBrake-N-Go (hand)Dyreator presence starting systemHydrostaticHydraulic pumpsWheel motorsTuff Torq heavy-duly integrated piston wheel motorSpeed and direction controlTwin leversHydraulic ol coolerFilterInternal, replaceableHydraulic ol coolerFilter2x12.12Rear tiretesLoad rafting4PRBrakesDynamic brakingYwin leversPark brakeInternal, wel disk integrated in the transmissionPark brakeInternal, wel disk integrated in the transmissionProveSizeOblin, (fs2-cm) 7/ron TM PRO side-dischargeProveBrakeBrakeDynamic brakingProveTypeDischargeDeck construction25 in.DischargeIncorrents0.25 cnIncorrents0.25 cnIncorrents0.25 cnIncorrents0.25 cnIncorrents0.25 cnIncorrents0.25 cnIncorrents0.25 cnIncorrents0.25 cnIncorrents0.25 cnBiade tip speed130.5 c	Fuel tank capacity	11.5 U.S. gal.
Electrical system 20 amp Charge system 20 amp Battery voltage 12 V Cold cranking amp 300 amp Hour meter Standard, (gital Operator presence starting system Brake-N-Go (hand) Drivetrain Turl Torq heavy-duty integrated piston wheel motor Transmission Hydraulic pumps Wheel motors Turl Torq heavy-duty integrated piston wheel motor Speed and direction control Twin levers Hydraulic capacity 5.9 U.S. qt Filter Torq heavy-duty integrated piston wheel motor Trives 24x12-12 Rear tires Load rating 4 PR Brive wheels Rear tires Load rating Hour meters Dynamic braking Twin levers Park brake actuation Hour meters Dynamic braking Size Compared in the tarasmission Type Electro-magnetic, 225 lb-1t 305 Nm Size Deck construction Colin, (152-cm) 7iron TM PRO: 7-gauge, 0.179-in, (4.6-mm		
Charge system20 ampBattery voltage12 VCold cranking amp300 ampHour meterStandard, digitalOperator presence starting systemBrake-N-Go (hand)DivertainHydrostaicTransmissionWheel motorsTuff Torq heavy-duly integrated piston wheelMydraulic capacity5.9 U.S. qtHydraulic capacity5.9 U.S. qtHydraulic capacity5.9 U.S. qtHydraulic capacity5.9 U.S. qtFilterInternat. replaceableTiresUttersDrive wheelsRear tiresLoad ratingWin leversPark brakeTwin leversDrive wheelsPark brakeInternat. replaceableTiresUttersDrive wheelsPark brakeInternat. wet disk integrated in the transmissionPark brakeUttersDrive wheelsContractionPark brakeGold NameDriveSob NmDriveSob NmDriveSob NmDriveSol NmDriveSol NmMower decksIncorements0.25 in.Incorements0.25 in.Incorements0.25 in.Incorements0.25 in.Incorements0.25 in.Incorements0.46 cmIncorements0.46 cmIncorements0.46 cmIncorements0.46 cmIncorements0.46 cm		Yes
Battery voltage12 VCold cranking amp300 ampHour meterStandard, digitalOperator presence starting systemBrake-N-Co (hand)DrivetrainHurrasmissionTransmissionHydrostaticHydrostatic pumpsWheel motorsTuff Torq heavy-duty integrated piston wheelSpeed and direction controlTurin leversHydraulic oil coolerFilterInternal, replaceableFilterInternal, replaceableTresDrive wheels24x12-12Rear tiresLoad rating4PRBrakesDramic brakingInternal wet disk integrated in the transmissionPark brake actuationHand brakePark brake actuationHand brakeProElector-magnetic, 225 lb-ft 305 NmDriveSole, 0, 179-in, (4.6-mm) one-piece forged steelBischargeHeight-of-cut range1-5, 5 in,Increments0.26 in,Increments0.26 in,Increments0.26 in,Increments0.25 in,Increments0.26 in,Increments0.26 in,Increments0.26 in,Blade tip speedTrueWheels140 crankRating141 cranRating0.26 in,Increments0.26 in,Increments0.26 in,Increments0.26 in,Increments0.25 in,Increments0.26 in, <td>-</td> <td></td>	-	
Cold canking amp300 ampHour meterSandard, digitalOperator presence starting systemBrake-N-Go (hand)DriverainHydrostaticTransmissionHydrostaticHydraulic pumpsWheel motorsTuff Torq heavy-duty integrated piston wheelmotorTransmissionSpeed and direction controlTwin leversHydraulic capacity5.9 U.S. qtHydraulic coloerFilterInternal, replaceableDrive wheels24x12-12Rear tiresLoad rating4 PRBrakeInternal, replaceableTrasDynamic brakingYuni leversPark brake actuationHand brakePark brakeInternal wet disk integrated in the transmissionPark brake actuationHand brakePTOTypeSizeDrive00 hn. (152-cm) 71ron ** PRO side-dischargeProtecksSize0-In. (152-cm) 71ron ** PRO side-dischargeDirive0.25 in.Increments0.25 in.Increments0.25 in.Increments0.25 in.Increments0.25 in.Increments0.26 cmIncrements0.26 cmIncrements0.26 cmIncrements0.26 cmIncrements0.26 cmIncrements0.26 cmIncrements0.26 cmIncrements0.26 cmIncrements0.26 cmIncrements <td></td> <td>•</td>		•
Hour meterStandard, digital Deprator presence starting systemBrake-N-Go (hand)DrivetralTransmissionHydrostaticHydrostaticWheel motorsWheel motorsTuff Torq heavy-duty integrated piston wheel motorSpeed and direction controlTwin leversHydraulic oil cooler5.0 U.S. qtFilterInternal, replaceableTiresDrive wheelsRear tiresLoad rating4 PRBrakesInternal, replaceableType24x12-12Rear tiresLoad rating4 PRBrakesDydaring brake actuationTwin leversPark brakeInternal wet disk integrated in the transmissionPark brake actuationHond brakeProTypeElectro-magnetic, 225 lb-ft 305 NmDriveV-beitBize constructionDischargeIncrements0.25 in,Increments0.25 in,		
Operator presence starting systemBrake-N-Go (hand)DriverainHydrostaticTransmissionHydrostaticHydrotatic pumpsWheel motorsTuff Tora pheavy-duty integrated piston wheel motorSpeed and direction controlTwin leversHydraulic capacity5.9 U.S. qtHydraulic capacity5.9 U.S. qtHydraulic oil coolerFilterIntermal, replaceableTires24x12-12Drive wheels24x12-12Rear tires24x12-12Rear tiresLoad rating4 PRBrakesInternal wet disk integrated in the transmissionPark brakeInternal wet disk integrated in the transmissionPark brake actuationHand brakeProInternal wet disk integrated in the transmissionTypeSizeDriveVbeitMower docks		•
Driverial Hydroslatic Transmission Hydroslatic Transmission Hydroslatic Hydraulic pumps		-
Transmission Hydrostatic Hydraulic pumps Wheel motors Tuff forq heavy-duty integrated piston wheel motor Speed and direction control Twin levers Speed and direction control Twin levers Hydraulic capacity 5.9 U.S. qt Hydraulic capacity 5.9 U.S. qt Hydraulic capacity 2.8 U.S. qt Hydraulic capacity 2.8 U.S. qt Filter Internal, replaceable Tirres 24x12-12 Rear tires Load rating 24x12-12 Rear tires Load rating 24x12-12 Rear tires Load rating 4PR Brakes Internal wet disk integrated in the transmission Park brake actuation Had brake Drive V-belt Mower decks Size Size Size Deck construction Height-of-cut range 6-5 in. Increments 0.25 in. Increments 0.25 in. Increments 0.26 cm Increments <td></td> <td>Blake-IN-GO (Ilalia)</td>		Blake-IN-GO (Ilalia)
Hydraulic pumps		Hydrostatic
Wheel motors Tuff Torq heavy-duty integrated piston wheel motor Speed and direction control Twin levers Hydraulic capacity 5.9 U.S. qt Speed and direction control Twin levers Hydraulic capacity 5.9 U.S. qt Brace Internal, replaceable Hydraulic capacity 4.1 Brace 24x12-12 Rear tires Load rating 4.PR Brakes Internal wel disk integrated in the transmission Park brake Internal wel disk integrated in the transmission Park brake actuation Had brake Prof 305 Nm Drive Vabet Mower decks Electro-magnetic, 225 lb-ft Size 60-in. (152-cm) 710n TM PRO side-discharge Dick construction -nepiace forged steel Discharge - Height-of-cut range 1-55 in. Increments 0.25 cm Increments 0.26 cm Increments 0.26 cm Increments 0.25 in. Increments 0		
Speed and direction control Twin levers Speed and direction control Twin levers Hydraulic oil cooler Filter Internal, replaceable Tires Drive wheels Rear tires Load rating 4 PR Brakes Dynamic braking Twin levers Park brake actuation Hand brake Park brake actuation Hand brake Prop Electro-magnetic, 225 lb-ft 305 Nm V-belt Mower decks 305 Nm Drive V-belt Mower decks Size 60-in. (152-cm) 7lron ™ PRO side-discharge Dirke V-belt Mower decks Size 025 in. Dirker V-belt Mower decks Size 026 in. Discharge Height-of-cut range 1-5.5 in. Increments 0.25 cm Increments <td></td> <td>Tuff Torg heavy-duty integrated piston wheel</td>		Tuff Torg heavy-duty integrated piston wheel
Hydraulic capacity5.9 U.S. qtHydraulic cil coolerFilterInternal, replaceableTires4x12-12Rear tiresLoad rating4yRBrakesDynamic brakingTwin leversPark brakeInternal wet disk integrated in the transmissionPark brake actuationTwin leversPark brake actuationElectro-magnetic, 225 lb-ftDrive305 NmDriveV-beltMover decksSizeGo-in, (152-cm) 7tron TM PRO side-dischargeDeck construction7-Iron TM PRO: 7-gauge, 0.179-in, (4.6-mm) one-plece forged steelDischargeHeight-of-cut range1-55 in.Increments0.25 in.Deck construction1-70 PRO: Approximately 18,500 fpmNumberThreeEladesFat freeCaster wheel size136.5-6Front anti-scalp rollersStandardRear anti-scalp rollersStandardWitchWitt chute down, 68, 74, 86 in.WittWitt chute down, 68, 74, 86 in.		
SizeSizeSizeDischarge	Speed and direction control	Twin levers
Hydraulic oil cooler Filter Internal, replaceable Thres 24x12-12 Rear tires Load rating 4 PR Brakes Dynamic braking Twin levers Park brake Internal wet disk integrated in the transmission Park brake actuation Hand brake Proper Electro-magnetic, 225 lb-ft Join Ne Velt Mower decks Size 60-in. (152-cm) 7lron TM PRO side-discharge Dick construction Discharge Height-of-cut range 15.5 in. Increments 0.25 in. Increments 0.25 in. Increments 0.25 cm Increments 0.25 in. Increments 0.25 in. Increments 0.25 in. Increments 0.26 cm Increments 0.26 cm Increments 0.26 in. Increments 0.26 in. Increments 0.26 in. Increments 0.26 in.	Hydraulic capacity	5.9 U.S. qt
FilterInternal, replaceableTiresUniverationDrive wheels4x12-12Rear tiresLoad rating4PRBrakesDynamic brakingTwin leversPark brakeInternal wet disk integrated in the trasmissionPark brakeInternal wet disk integrated in the trasmissionPark brakeElectro-magnetic, 225 lb-ftTypeSo NmDriveV-bettDriveOf NmDriveBack construction60-in. (152-cm) 7lron TM PRO side-discharge Deck constructionIncrements0.25 cmIncrements0.25 in.Increments0.25 cmIncrements0.25 in.Increments0.25 in.Increments0.26 in.Increments0		5.6 L
Tires Drive wheels 24x12-12 Rear tires	Hydraulic oil cooler	
Drive wheels 24x12-12 Rear tires	Filter	Internal, replaceable
Rear tires Load rating 4 PR Brakes Dynamic braking Twin levers Park brake Internal wet disk integrated in the transmission Park brake actuation Hand brake Park brake actuation Hand brake Park brake actuation Hand brake PTO Electro-magnetic, 225 lb-ft Jorse State Drive V-belt Mower decks State 60-in. (152-cm) 7lron TM PRO side-discharge Drive V-belt Mower decks Black construction 7-lron TM PRO: 7-gauge, 0.179-in. (4.6-mm) one-piece forged steel Discharge Height-of-cut range 1-55 in. Increments 0.25 in. Increments 0.25 in. Increments 0.25 m. Increments 0.25 m. Increments 0.25 in. Increments 0.25 in. Blades Quaries by deck size Thickness 0.25 in. Blade tip speed Nion PRO: Approximately 18,500 fpm Number Three Caster wheel type Flat free Caster wheels 13x6 5-6 Fort an		
Load rating 4 PR Brakes Twin levers Park brake Internal wet disk integrated in the transmission Park brake actuation Hand brake Park brake actuation Internal wet disk integrated in the transmission Park brake actuation Hand brake Park brake actuation Internal wet disk integrated in the transmission Park brake actuation Hand brake Park brake actuation Biotecommetry action Prof Electro-magnetic, 225 lb-ft Drive V-belt Drive V-belt Drive V-belt Drive V-belt Bize 60-in. (152-cm) 7/ron™ PRO side-discharge Deck construction Discharge Height-of-cut range 0-in. (152-cm) 7/ron™ PRO side-discharge Increments 0.25 in. Increments 0.25 in. </td <td></td> <td></td>		
Brakes Twin levers Park brake Internal wet disk integrated in the transmission Park brake actuation Hand brake Park brake actuation Hand brake Park brake actuation Electro-magnetic, 225 lb-ft 305 Nm Jonamic Draw Pro Electro-magnetic, 225 lb-ft Jorke actuation Color. (152-cm) 7lron™ PRO side-discharge Prive Oo-in. (152-cm) 7lron™ PRO side-discharge Discharge Height-of-cut range 0-in. (152-cm) 7lron™ PRO side-discharge Increments 0.25 in. Increments 0.25 in. Increments 0.25 in. Increments 0.25 cm Increments 0.24 cm Increments 0.25 cm Increments 0.25 in. Increments 0.24 cm Increments 0.24 cm Increments 0.25 in. Increments 0.25 in. Increments		
Dynamic braking Twin levers Park brake Internal wet disk integrated in the transmission Park brake actuation Hand brake Park brake actuation Hand brake PTO Electro-magnetic, 225 lb-ft Jype Biotro-magnetic, 225 lb-ft Drive V-belt Wower decks 60-in. (152-cm) 7lron™ PRO side-discharge Deck construction 7-iron™ PRO: 7-gauge, 0.179-in. (4.6-mm) one-piece forged steel Discharge Height-Of-cut range 1-5.5 in. Increments 0.25 in. Increments 0.25 cm Increments 0.25 cm Increments 0.25 cm Increments 0.25 cm Increments 0.26 cm Increments 0.25 cm Increments 0.25 cm Increments 0.25 cm Increments 0.26 cm Increments 0.26 cm Increments 0.26 cm Increments 0.26 cm With speed 71 ron PRO: Approximately 18,500 fpm	5	4 PR
Park brake Internal wet disk integrated in the transmission Park brake actuation Hand brake PrO Electro-magnetic, 225 lb-ft Type Electro-magnetic, 225 lb-ft Drive V-belt Mower decks Electro-magnetic, 225 lb-ft Size 60-in, (152-cm) 7Iron™ PRO side-discharge Deck construction 7-Iron™ PRO: 7-gauge, 0.179-in. (4.6-mm) one-piece forged steel Discharge Height-of-cut range 1.55 in. Increments 0.25 in. Increments 0.25 cm Increments 0.26 cm Cutting width 54, 60, 72 in. Increments 0.26 cm Cutting width 54, 60, 72 in. Blades 137, 152, 183 cm Blades 1000000000000000000000000000000000000		
Park brake actuation Hand brake PTO Hand brake Type Electro-magnetic, 225 lb-ft Jorive V-bett Mower decks 60-in. (152-cm) 7lron™ PRO side-discharge Dirke 60-in. (152-cm) 7lron™ PRO side-discharge Deck construction 7-lron™ PRO: 7-gauge, 0.179-in. (4.6-mm) Discharge	, ,	
PTO Type Electro-magnetic, 225 lb-ft Jorive 305 Nm Drive V-belt Mower decks 60-in. (152-cm) 7lron™ PRO side-discharge Deck construction 7-lron™ PRO: 7-gauge, 0.179-in. (4.6-mm) Discharge Height-of-cut range 1-5.5 in. Increments 0.25 in. Increments 0.25 cm Increments 0.64 cm Blades 0.45 cm Length Varies by deck size Thickness 0.25 in. Gaster wheels 13rch PRO: Approximately 18,500 fpm Number Three Wheels Standard Gaster wheels 13rch S-6 <		5
Type Electro-magnetic, 225 lb-ft Jorive 305 Nm Drive V-belt Mower decks 60-in. (152-cm) 7Iron™ PRO side-discharge Deck construction 7-Iron™ PRO: 7-gauge, 0.179-in. (4.6-mm) Discharge ~ Height-of-cut range 1-5.5 in. Increments 0.25 in. Increments 0.25 cm Increments 0.26 cm Increments 0.64 cm Increments 0.64 cm Increments 0.64 cm Cutting width 54.60, 72 in. Eength Caster wheels Increments 0.64 cm Increments 0.64 cm Increments 0.25 in. Increments 0.64 cm Increments 0.64 cm Increments 0.25 in. Increments 0.64 cm Increments <td>Park brake actuation</td> <td>Hand brake</td>	Park brake actuation	Hand brake
Joine 305 Nm Drive V-belt Mower decks 60-in. (152-cm) 7Iron™ PRO side-discharge Deck construction 7-Iron™ PRO: 7-gauge, 0.179-in. (4.6-mm) one-piece forged steel Discharge Height-of-cut range 1-5.5 in. Increments 0.25 in. Increments 0.64 in. Increments 0.64 cm Cutting width 54, 60, 72 in. Increments 0.64 cm Cutting width 54, 60, 72 in. Height-Speed 71ron PRO: Approximately 18,500 fpm Number Varies by deck size Blade tip speed 71ron PRO: Approximately 18,500 fpm Number Three Wheels 13x6.5-6 Front anti-scalp rollers RH, center, LH Rear anti-scalp rollers RH, center, LH Rear anti-scalp rollers 84 in. 213 cm 213 cm	РТО	
Drive V-belt Bower decks 60-in. (152-cm) 71ron™ PRO side-discharge Size 60-in. (152-cm) 71ron™ PRO: 7-gauge, 0.179-in. (4.6-mm) Discharge Height-of-cut range Height-of-cut range 1-5.5 in. Increments 0.25 in. Increments 0.64 in. Increments 0.25 cm Increments 0.64 cm Cutting width 54, 60, 72 in. Increments 0.64 cm Cutting width 54, 60, 72 in. Braces 0.64 cm Thickness 0.25 in. Increments 0.64 cm Blade tip speed 71ron PRO: Approximately 18,500 fpm Number 71ron PRO: Approximately 18,500 fpm Number 10:64 cm Blade tip speed 71ron PRO: Approximately 18,500 fpm Number 13x6.5-6 Front anti-scalp rollers 13x6.5-6 Front anti-scalp rollers 84 in. Rear anti-scalp rollers 84 in. Witt 213 cm Witt Witt chute down, 68, 74, 86 in.	Туре	Electro-magnetic, 225 lb-ft
Mover decks 60-in. (152-cm) 7lron™ PRO side-discharge Size 60-in. (152-cm) 7lron™ PRO side-discharge Deck construction 7-lron™ PRO: 7-gauge, 0.179-in. (4.6-mm) one-pice forged steel Discharge Height-of-cut range 1-5.5 in. Increments 0.25 in. Increments 0.25 cm Increments 0.64 in. Increments 0.64 cm Cutting width 54, 60, 72 in. Thickness 0.25 in. Unique the pice 137, 152, 183 cm Blades 0.25 in. Length Varies by deck size Thickness 0.25 in. 0.64 cm 0.64 cm Blade tip speed 7lron PRO: Approximately 18,500 fpm Number Varies by deck size Thickness 0.64 cm Blade tip speed 7lron PRO: Approximately 18,500 fpm Number Heels Caster wheel type Flat free Caster wheels 13x6.5-6 Front anti-scalp rollers RH, center, LH Rear anti-scalp rollers RH, center, LH Rear anti-scalp rollers 84 in. Lange 213 cm Witth Wit chute down, 68, 74, 86 in.		305 Nm
Size 60-in. (152-cm) 7lron™ PRO side-discharge Deck construction 7-lron™ PRO: 7-gauge, 0.179-in. (4.6-mm) one-piece forged steel Discharge Height-of-cut range 1-5.5 in. Increments 0.25 in. Increments 0.64 in. Increments 0.64 in. Increments 0.64 cm Increments 0.64 cm Increments 0.64 cm Increments 0.64 cm Blade tip speed 7lron PRO: Approximately 18,500 fpm Number Varies by deck size Gaster wheel type Flat free Caster wheels 13x6.5-6 Front anti-scalp rollers RH, center, LH Rear anti-scalp rollers 84 in. Lemsh 213 cm Witth Witt chute down, 68, 74, 86 in.	Drive	V-belt
Deck construction 7-Iron™ PRO: 7-gauge, 0.179-in. (4.6-mm) one-piece forged steel Discharge Height-of-cut range 1-5.5 in. Increments 0.25 in. Increments 0.64 in. Increments 0.64 cm Cutting width 54, 60, 72 in. Increments 0.64 cm Cutting width 54, 60, 72 in. Blades 137, 152, 183 cm Length Varies by deck size Thickness 0.25 in. 0.64 cm 0.64 cm Bladets 0.64 cm Length Varies by deck size Thickness 0.25 in. 0.64 cm 0.64 cm Blade tip speed 71ron PRO: Approximately 18,500 fpm Number Three Wheels 13x6.5-6 Front anti-scalp rollers RH, center, LH Rear anti-scalp rollers RH, center, LH Rear anti-scalp rollers 84 in. 213 cm With chute down, 68, 74, 86 in.		
DischargeHeight-of-cut range1-5.5 in.Increments0.25 in.Increments0.64 in.2.54-14 cm2.54-14 cmIncrements0.25 cmIncrements0.64 cmCutting width54, 60, 72 in.Thickness0.25 in.Blades137, 152, 183 cmBlades0.25 in.LengthVaries by deck sizeThickness0.25 in.Blade tip speed71ron PRO: Approximately 18,500 fpmNumberThreeWheels13x6.5-6Front anti-scalp rollersRH, center, LHRear anti-scalp rollersRH, center, LHRear anti-scalp rollers84 in.213 cmWith chute down, 68, 74, 86 in.		–
Discharge	Deck construction	
Height-of-cut range 1-5.5 in. Increments 0.25 in. Increments 0.64 in. Increments 0.25 cm Increments 0.64 cm Cutting width 54, 60, 72 in. Cutting width 54, 60, 72 in. Thickness 0.25 in. Length Varies by deck size Thickness 0.25 in. Blade tip speed 7lron PRO: Approximately 18,500 fpm Number Three Wheels 13x6.5-6 Front anti-scalp rollers RH, center, LH Rear anti-scalp rollers Standard Dimensions 84 in. With With chute down, 68, 74, 86 in.	Discharge	
Increments	-	1-5 5 in
Increments0.64 in.Increments2.54-14 cmIncrements0.25 cmIncrements0.64 cmCutting width54, 60, 72 in.Ture137, 152, 183 cmBlades137, 152, 183 cmIncrements0.25 in.Thickness0.25 in.Blade tip speed71ron PRO: Approximately 18,500 fpmNumberThreeWheels13x6.5-6Front anti-scalp rollersRH, center, LHRear anti-scalp rollersStandardDimensions84 in.WidthWith chute down, 68, 74, 86 in.		
Increments 2.54-14 cm Increments 0.25 cm Cutting width 54, 60, 72 in. Cutting width 54, 60, 72 in. Cutting width 54, 60, 72 in. Blades 137, 152, 183 cm Ength Varies by deck size Thickness 0.25 in. Thickness 0.25 in. Blade tip speed 7lron PRO: Approximately 18,500 fpm Number Three Wheels 2 Caster wheel type Flat free Caster wheels 13x6.5-6 Front anti-scalp rollers RH, center, LH Rear anti-scalp rollers Standard Dimensions 213 cm Width With chute down, 68, 74, 86 in.		
Increments 0.64 cm Cutting width 54, 60, 72 in. 137, 152, 183 cm 137, 152, 183 cm Blades Varies by deck size Length Varies by deck size Thickness 0.25 in. Thickness 0.64 cm Blade tip speed 7lron PRO: Approximately 18,500 fpm Number Three Wheels Caster wheel type Caster wheels 13x6.5-6 Front anti-scalp rollers RH, center, LH Rear anti-scalp rollers Standard Dimensions 44 in. Utith With chute down, 68, 74, 86 in.		
Cutting width 54, 60, 72 in. 137, 152, 183 cm Blades Length Varies by deck size Thickness 0.25 in. Thickness 0.64 cm Blade tip speed 7lron PRO: Approximately 18,500 fpm Number Three Wheels 54, 60, 72 in. Caster wheel type Flat free Caster wheels 13x6.5-6 Front anti-scalp rollers RH, center, LH Rear anti-scalp rollers Standard Dimensions 213 cm Width With chute down, 68, 74, 86 in.	Increments	0.25 cm
Blades 137, 152, 183 cm Length Varies by deck size Thickness 0.25 in. Thickness 0.64 cm Blade tip speed 7lron PRO: Approximately 18,500 fpm Number Three Wheels Caster wheel type Caster wheels 13x6.5-6 Front anti-scalp rollers RH, center, LH Rear anti-scalp rollers Standard Dimensions 213 cm Width With chute down, 68, 74, 86 in.	Increments	0.64 cm
Blades Varies by deck size Length Varies by deck size Thickness 0.25 in. Thickness 0.64 cm Blade tip speed 7lron PRO: Approximately 18,500 fpm Number Three Wheels Easter wheel type Caster wheels 13x6.5-6 Front anti-scalp rollers RH, center, LH Rear anti-scalp rollers Standard Dimensions 213 cm Width With chute down, 68, 74, 86 in.	Cutting width	54, 60, 72 in.
Length Varies by deck size Thickness 0.25 in. D.46 cm 0.64 cm Blade tip speed 7lron PRO: Approximately 18,500 fpm Number Three Wheels E Caster wheel type Flat free Caster wheels 13x6.5-6 Front anti-scalp rollers RH, center, LH Rear anti-scalp rollers Standard Dimensions 213 cm Width With chute down, 68, 74, 86 in.		137, 152, 183 cm
Thickness 0.25 in. 0.64 cm 0.64 cm Blade tip speed 7Iron PRO: Approximately 18,500 fpm Number Three Wheels Easter wheel type Caster wheels 13x6.5-6 Front anti-scalp rollers RH, center, LH Rear anti-scalp rollers Standard Dimensions 84 in. 213 cm With chute down, 68, 74, 86 in.		
0.64 cmBlade tip speed7lron PRO: Approximately 18,500 fpmNumberThreeWheelsThreeCaster wheel typeFlat freeCaster wheels13x6.5-6Front anti-scalp rollersRH, center, LHRear anti-scalp rollersStandardDimensions213 cmWidthWith chute down, 68, 74, 86 in.	•	-
Blade tip speed 7Iron PRO: Approximately 18,500 fpm Number Three Wheels Elat free Caster wheel type Flat free Caster wheels 13x6.5-6 Front anti-scalp rollers RH, center, LH Rear anti-scalp rollers Standard Dimensions 84 in. 213 cm With chute down, 68, 74, 86 in.	Thickness	
Number Three Wheels Flat free Caster wheel type Flat free Caster wheels 13x6.5-6 Front anti-scalp rollers RH, center, LH Rear anti-scalp rollers Standard Dimensions 84 in. 213 cm With chute down, 68, 74, 86 in.		
Wheels Flat free Caster wheel type Flat free Caster wheels 13x6.5-6 Front anti-scalp rollers RH, center, LH Rear anti-scalp rollers Standard Dimensions 84 in. 213 cm 213 cm Width With chute down, 68, 74, 86 in.		
Caster wheel type Flat free Caster wheels 13x6.5-6 Front anti-scalp rollers RH, center, LH Rear anti-scalp rollers Standard Dimensions 213 cm Width With chute down, 68, 74, 86 in.		
Caster wheels 13x6.5-6 Front anti-scalp rollers RH, center, LH Rear anti-scalp rollers Standard Dimensions 84 in. 213 cm 213 cm Width With chute down, 68, 74, 86 in.		Flat free
Rear anti-scalp rollers Standard Dimensions 84 in. 213 cm Width With chute down, 68, 74, 86 in.		
Rear anti-scalp rollers Standard Dimensions 84 in. 213 cm Width With chute down, 68, 74, 86 in.		
84 in. 213 cm Width With chute down, 68, 74, 86 in.	Rear anti-scalp rollers	Standard
213 cmWidthWith chute down, 68, 74, 86 in.	Dimensions	
WidthWith chute down, 68, 74, 86 in.		
Confidential	Width	
		Confidential



	173, 188, 218 cm
Height	With ROPS up, 73 in.
	185 cm
Weight	1,296 to 1,412 lb
	588 to 640 kg
Buyer's note	-
Warranty	36 months or 1200 hours, whichever comes
	first
Key Specs	
Engine Manufacturer/model	FX850V
Engine power	Gross at 3,600 rpm
	27 hp
	20.1 kW
	11.5 U.S. gal.
	43.5 L
Mower deck size	60-in. (152-cm) 7Iron™ PRO side-discharge
	7Iron PRO: Approximately 18,500 fpm
	Hydrostatic
Speed range	0-10 mph
	0-16.1 km/h
	24x12-12
	13x6.5-6
	36 months or 1200 hours, whichever comes
	first
Operation	
Rollover protective structure (ROPS)	Yes
Slope operating limit	20 degrees (10 degrees with material
	collection system installed)
Additional information	
Date collected	15-Mar-2023