

0		4 _		 _
	us	tΛ	m	

Quotes are valid for 30 days from the creation date or upon contract expiration, whichever occurs first.

A Purchase Order (PO) or Letter of Intent (LOI) including the below information is required to proceed with this sale. The PO or LOI will be returned if information is missing.

Vendor: Deere & Company	For any questions, please contact:			
2000 John Deere Run Cary, NC 27513	Jerrod Haas			
Signature on all LOIs and POs with a signature line	Shiloh Valley Equipment Co. 4050 East Highway 161 Belleville, IL 62221			
Contract name or number; or JD Quote ID	Tel: 618-744-0433			
Sold to street addressShip to street address (no PO box)	Fax: 618-744-0443 Email: lgsales@shiloh-valley.com			
☐ Bill to contact name and phone number				
☐ Bill to address				
Bill to email address (required to send the in exemption certificate	voice and/or to obtain the tax			
Membership number if required by the contra	act			

Quotes of equipment offered through contracts between Deere & Company, its divisions and subsidiaries (collectively "Deere") and government agencies are subject to audit and access by Deere's Strategic Accounts Business Division to ensure compliance with the terms and conditions of the contracts.



ALL PURCHASE ORDERS MUST BE MADE OUT TO (VENDOR):

Deere & Company 2000 John Deere Run Cary, NC 27513 FED ID: 36-2382580 UEID: FNSWEDARMK53

ALL PURCHASE ORDERS MUST BE SENT TO DELIVERING DEALER:

Shiloh Valley Equipment Co. 4050 East Highway 161 Belleville, IL 62221 618-744-0433

shilohvalley@shiloh-valley.com

Quote Summary

Prepared For: CITY OF LEBANON 312 W SAINT LOUIS ST

LEBANON, IL 62254 Business: 618-537-4976 streets@lebanonil.org Delivering Dealer: Shiloh Valley Equipment Co.

Jerrod Haas 4050 East Highway 161 Belleville, IL 62221 Phone: 618-744-0433 Igsales@shiloh-valley.com

Quote ID: 29013627 Created On: 09 June 2023 Last Modified On: 09 June 2023 Expiration Date: 10 July 2023

Equipment Summary Suggested List Selling Price Qty Extended

JOHN DEERE Z950M ZTrak \$11,474.00 \$7,687.58 X 1 = \$7,687.58

Contract: IL PSD Mowers 4018512 (PG 97 CG 22)

Price Effective Date: September 4, 2017

Equipment Total \$ 7,687.58

* Includes Fees and Non-contract items	Quote Summary			
	Equipment Total	\$ 7,687.58		
	Trade In			
	SubTotal	\$ 7,687.58		
	Est. Service Agreement Tax	\$ 0.00		
	Total	\$ 7,687.58		
	Down Payment	(0.00)		
	Rental Applied	(0.00)		
	Balance Due	\$ 7,687.58		

Salesperson: X _____ Accepted By: X _____



Selling Equipment

Quote Id: 29013627 **Customer Name: CITY OF LEBANON**

ALL PURCHASE ORDERS MUST BE MADE OUT TO (VENDOR):

Deere & Company 2000 John Deere Run Cary, NC 27513 FED ID: 36-2382580 **UEID: FNSWEDARMK53** ALL PURCHASE ORDERS MUST BE SENT

TO DELIVERING DEALER: Shiloh Valley Equipment Co. 4050 East Highway 161 Belleville, IL 62221 618-744-0433 shilohvalley@shiloh-valley.com

JOHN	DEERE	Z950M	ZTrak

Hours: Suggested List *

Stock Number: \$ 11,474.00

Contract: IL PSD Mowers 4018512 (PG 97 CG 22) Selling Price *

\$ 7 687 58 Price Effective Date: Sentember 1 2017

Price Effective Date: September 4, 2017 \$ 7,687.58							
	,	* Pri	ce per item	- includes F	ees and No	n-contract i	tems
Code	Description	Qty	List Price	Discount%	Discount Amount	Contract Price	Extended Contract Price
0694TC	Z950M ZTrak	1	\$ 10,999.00	33.00	\$ 3,629.67	\$ 7,369.33	\$ 7,369.33
Standard Options - Per Unit							
001A	United States/Canada	1	\$ 0.00	33.00	\$ 0.00	\$ 0.00	\$ 0.00
1036	24x12x12 Pneumatic Turf Tire for 54 In. and 60 In. Decks	1	\$ 0.00	33.00	\$ 0.00	\$ 0.00	\$ 0.00
1504	60 In. Side Discharge Mower Deck	1	\$ 0.00	33.00	\$ 0.00	\$ 0.00	\$ 0.00
2093	Fully Adjustable Suspension Seat with Armrests (24" High Back)	1	\$ 475.00	33.00	\$ 156.75	\$ 318.25	\$ 318.25
	Standard Options Total		\$ 475.00		\$ 156.75	\$ 318.25	\$ 318.25
	Value Added Services Total		\$ 0.00			\$ 0.00	\$ 0.00
Total Selling Price			\$ 11,474.00		\$ 3,786.42	\$ 7,687.58	\$ 7, 6 87.58



Product features, prices and specifications are based on published information at the time of publication and are subject to change without notice. All trademarked terms, including John Deere, the leaping deer symbol and the colors green and yellow used herein are the property of Deere & Company, unless otherwise noted. Products, product features, and other content on this site may only be accurate for products marketed and sold in North America.

Copyright ?? 1994- 2023 Deere & Company. All Rights Reserved.

File Created: 09-Jun-2023

2023 JOHN DEERE Z950M ZTrak

Key Features

Powerful 27-hp (20.1-kW) commercial-grade engine delivers class-leading performance and efficiency

The Z950M and Z950R are powered by an air-cooled, vertical shaft engine:

• 27-hp (20.1-kW) gas engine

Engine features include:

- · Overhead valve design
- · More horsepower and torque per cubic inch of displacement
- · Better fuel efficiency
- Full-pressure lubrication with full-flow filter
- Reduces engine wear by ensuring proper lubrication, even when operating on hillsides or uneven terrain
- · Oil filter helps keep oil clean for increased engine life
- · V-twin big block design
- · Vertical shaft
- · Easy-access, dual-element air filter with quick-release latch
- 15-amp alternator
- Fuel pump
- Complies with strict Environmental Protection Agency (EPA) and California Air Resources Board (CARB) emission standards without loss of horsepower or torque
- · Aluminum block engines
- Effectively dissipate heat
- Lightweight and strong construction
- Extend engine life due to elimination of debilitating engine temperatures
- Air-cooled engine design



Z950M and Z950R engine

Base Equipment On: Z950M, Z950R

Air cleaner filters out dust that can damage an engine

ZTrak™ Z900 Mowers are equipped with a dual-element, canister-style air filter, easily accessible from the rear of the machine without tools.

- The filtration system pulls clean air from above the engine, in turn filtering out the dust that can damage an engine over time.
- Filters are extremely easy to change when required.
- Pre-cleaner provides more protection against contamination in dusty and dirty applications.









Air cleaner cover removed

Base Equipment On: Z950M, Z950R

Mow all day on a single tank of fuel with efficient and easy-to-fill fuel tank

The ZTrak™ Z900 Mowers are equipped with one single-fill, top-draw fuel tank:

- 11.5-U.S. gal. (43.5-L) capacity enables operators to mow all day without refueling.
- The fuel gauge makes it quick and easy to see how much fuel is in the tank.
- Top draw provides added safety.
- A large fuel-filler neck is angled to make it easy for an operator to complete the fueling process. Under normal conditions, load, and operation, fuel consumption for the Z900 ZTrak Mowers is 1.5 U.S. gph (5.7 L/hr) to 2.2 U.S. gph (8.3 L/hr), depending on the horsepower and conditions.



Fuel tank and filler neck



Fuel filler neck

Base Equipment On: Z950M, Z950R

Key Features

Three-year, bumper-to-bumper warranty









Z930R ZTrak Mower

Base Equipment On: Z915E, Z920M, Z930M, Z945M EFI, Z950M, Z955M EFI, Z960M, Z930R, Z950R, Z955R EFI, Z970R E and M Series 3-year, 1200-hour bumper-to-bumper warranty

An exclusive 2-year, unlimited hour/3-year, 1200-hour (whichever comes first) bumper-to-bumper warranty is standard for all John Deere E and M Series Mowers. The warranty is best in its class and places John Deere at the forefront of commercial mowing. It is also hassle free, with one company handling all of the paperwork.

NOTE: 36 months or 1200 hours, whichever comes first. For the first 24 months, there is no hour limitation.

Base Equipment On: Z915E, Z920M, Z930M, Z945M EFI, Z950M, Z955M EFI, Z960M, Z930R, Z950R, Z955R EFI, Z970R R Series 3-year, 1500-hour bumper-to-bumper warranty

An exclusive 2-year, unlimited hour/3-year, 1500-hour (whichever comes first) bumper-to-bumper warranty is standard on all John Deere R Series mowers. The warranty is best in the industry and puts John Deere at the forefront of commercial mowing. It is also hassle free, with one company handling all of the paperwork.

NOTE: 36 months or 1500 hours, whichever comes first. For the first 24 months, there is no hour limitation.

Base Equipment On: Z915E, Z920M, Z930M, Z945M EFI, Z950M, Z955M EFI, Z960M, Z930R, Z950R, Z955R EFI, Z970R



Mowers decks are evaluated by the manufacturer (John Deere Turf Care) and conform to American National Standards Institute (ANSI) B71.4 2004 safety certification specifications for commercial turf care equipment.

54-in. (137-cm) 7-Iron PRO Mower Deck

Base Equipment On: Z915E, Z920M, Z930M, Z945M EFI, Z950M, Z955M EFI, Z960M, Z930R, Z950R, Z955R EFI, Z970R

Key Features

Heavy-duty frame provides strength and durability






Z970R shown with optional X® Tweel® Turf airless radial tire technology

The durability features of the frame are as follows:

- · Heavy-duty, thick-gauge, steel channel mainframe for strength and durability
- Cast I-beam caster arms to handle the beating and pounding professional mowers receive
- · Wide-open access for maintenance and cleaning

Base Equipment On: Z915E, Z920M, Z930M, Z945M EFI, Z950M, Z955M EFI, Z960M, Z930R, Z950R, Z955R EFI, Z970R **Two-piece rear bumper provides protection**



A steel rear bumper provides protection for the machine. The bumper is made of two pieces, making it easy to remove and install when using a material collection system (MCS).

A rear hitch can be added to the steel bumper for towing purposes. ZTrak E, M, and R Series Mowers can tow up to 400 lb (181.4 kg).

Michelin, X, and Tweel are trademarks of Michelin North America, Inc.

Illustration of ZTrak™ mower rear bumper

Base Equipment On: Z915E, Z920M, Z930M, Z945M EFI, Z950M, Z955M EFI, Z960M, Z930R, Z950R, Z955R EFI, Z970R

Product Specification Details:

MankoflanctiDezere Z950M (Model year 2023)

Model Engine

Manufacturer/Model FX850V

Power Gross at 3,600 rpm

27 hp 20.1 kW 52 cu in.

Cylinders

852 cc Two

Crankcase capacity

Displacement

With filter, 2.4 U.S. qt

2.3 L

Oil filter Full flow, replaceable
Lubrication Full pressure
Cooling Air

Cooling
Air cleaner

ner Heavy-duty canister type with safety element

Pre-cleaner



Fuel system

Fuel type Gasoline

Fuel consumption Under normal conditions, load, operation, and

dependent on loads and operating conditions

1.1-1.9 U.S. gal./hr 4.2-7.2 L/hr

Fuel tank capacity 11.5 U.S. gal. 43.5 L

Fuel tank switch/shut-off valve

Electrical system

20 amp Charge system Battery voltage 12 V Cold cranking amp 300 amp Hour meter Standard, digital Brake-N-Go (hand)

Operator presence starting system

Speed and direction control

Drivetrain

Transmission Hydrostatic Hydraulic pumps

Tuff Torq heavy-duty integrated piston wheel Wheel motors

> Twin levers 5.9 U.S. qt

> > Internal, replaceable

Hydraulic capacity 5.6 L Hydraulic oil cooler

Filter Tires

> Drive wheels 24x12-12 Rear tires 4 PR Load rating

Brakes

Dynamic braking Twin levers

Park brake Internal wet disk integrated in the

transmission

Park brake actuation Hand brake

PTO

Туре Electro-magnetic, 225 lb-ft

> 305 Nm V-belt

Drive Mower decks

Size

60-in. (152-cm) 7Iron™ PRO side-discharge Deck construction 7-Iron™ PRO: 7-gauge, 0.179-in. (4.6-mm)

one-piece forged steel

Discharge Height-of-cut range Increments Increments

1-5.5 in. 0.25 in. 0.64 in. 2.54-14 cm 0.25 cm

Increments Increments 0.64 cm Cutting width 54, 60, 72 in. 137, 152, 183 cm

Blades

Length Varies by deck size

0.25 in. Thickness 0.64 cm

Blade tip speed 7Iron PRO: Approximately 18,500 fpm

Number Three

Wheels

Caster wheel type Flat free Caster wheels 13x6.5-6 Front anti-scalp rollers RH, center, LH Rear anti-scalp rollers Standard

Dimensions

84 in. 213 cm

Width With chute down, 68, 74, 86 in.



173, 188, 218 cm

With ROPS up, 73 in. Height

185 cm

1,296 to 1,412 lb Weight 588 to 640 kg

Buyer's note

Warranty 36 months or 1200 hours, whichever comes

Key Specs

Engine Manufacturer/model FX850V

Engine power Gross at 3,600 rpm

> 27 hp 20.1 kW 11.5 U.S. gal. 43.5 L

60-in. (152-cm) 7Iron™ PRO side-discharge Mower deck size

7Iron PRO: Approximately 18,500 fpm

Hydrostatic

0-16.1 km/h 24x12-12 13x6.5-6

0-10 mph

36 months or 1200 hours, whichever comes

first

Operation

Speed range

Rollover protective structure (ROPS) Yes

Slope operating limit 20 degrees (10 degrees with material

collection system installed)

Additional information

Date collected 15-Mar-2023